ಕರ್ನಾಟಕದ ಪ್ರಥಮ ಹಮ್ಮೆಯ ಉತ್ಪಾದನೆ ಲಿಥಿಯಂ ಯುಪಿಎಸ್











Why is Basukey your best choice?

Zero Maintenance

4 years of warranty

10 years of battery life

2500 battery life cycles

Just 22 kg in weight

Easy portable design

No distilled water

No sulfuric acid

Zero Liquid Chemical Process

Fit & Forget Product

Charging time is only 5–6 hours

It's a totally eco-friendly product

Pure sine wave output

Built-in BMS protection

Forever safer than a lead-acid battery

Load Protection from High or Low Voltage

Easy wall-mounting design

No hazardous fume generation

Very little space consumption

Lithium Battery Inbuilt Design

Very little charging power consumption

It's totally contamination-free energy

Noiseless Operation in All Loads

Double Exaust fan protection

Natural cooling product
True Capacity Performing Battery

Digital Display with LED Indications

Light in Weight, Sleek in Size

Long-life transformer-based circuit design

Unbrakable 3-pin top

Easy-to-repair PCB components

with through-hole technology

Safety Features in Basukey Lithium UPS

- Overload Protection
- Cell Balancing Protection
- Penetration Protection
- Thermal Shock Protection
- Over charge Protection
- Deep Discharge Protection
- Short Circuit Protection
- Reverse Polarity Protection
- Over Current Protection
 - Over Temperature Protection
 - DC & AC Fuse Protection Low & High volt Cut off Protection

BK1250





BK2000 & BLF2000 Combo





Fit & Forget Product

BK3000 & BLF4000 Combo







BK5000 & BLF6000 Combo





BK7500 & BLF6000 Combo





BK10000 & BLF10000 Combo







Basukey Lith	nium U	PS Tech	nnical S	pecific	ations
Description	BK1250	BK2000	BK3000	BK5000	BK7500

2000

1600

25.6

Mains Mode

UPS Mode

27.5

22.4

3000

2400

51.2

125-280V AC±10V

Same as Input

Same as Input

220V±5%

50 Hz±0.1 Hz

Sinewave

Automatic

15A±3A

Constant Current Constant Voltage

<15ms

55.0

46.0

85.2

63.6

85.2

63.6

External Single Battery Pack

Only Ground Vertical Mounting

5000

4000

76.8

7500

6000

76.8

1250

1000

12.8

Inbuilt

Wall

14.2

11.2

Capacity in VA

Capacity in Watts

Battery DC Volts

Battery Position

Mounting Facility

Input Working Voltage

Output Voltage

Output Voltage Wave Form

Output Voltage

Output frequency

Output Voltage Wave Form

Changeover

Battery Charging Current

Charging High Cut Voltage

Charger Topology

Charging Low Cut Voltage

UPS transfer time

Description	BK1250	BK2000	BK3000	BK5000	BK7500
Weight in Kg	22	16	20	36	40
Size in Inches L X B X H	11 x 7 x 18	11 x 7 x 14	15 x 10 x 14	11 x 20 x 16	11 x 20 x 16
Description	BLF2000	BLF4000	BLF6000		
Weight in Kg	16	30	48		
Size in Inches L X B X H	11 x 7 x 14	13 x 8 x 18	15 x 12 x 16		

We are pleased to say that we have been at your service



Batteryking India Pvt Ltd

Corporate Office

#30/1, 3rd Cross, 3rd Main Rd, Dr Rajkumar Rd, opp. Raghavendra swami math, Prakash Nagar, Bengaluru, Karnataka 560021

Manufacturing Unit-A

1732, 1st E Main Rd, 2nd Stage, Rajajinagar, Bengaluru, Karnataka 560010

For Sales Helpline: 8277-885-777 sales@basukey.com
For Service Helpline: 8277-871-777 service@basukey.com

https://www.batteryking.in/ http://basukey.com/